

CEMENT PAINT

High Quality Acrylic Water-Based Paint For Cement Surfaces

Premium quality acrylic water-based paint for concrete surfaces for exterior use. Due to its special formula and alkali resistance it is recommended particularly for the painting and the protection of any cement surface such as exposed concrete. It provides great hiding power, high spreading capacity and exceptional fastness to frequent washing. It is easily applied with very good levelling properties providing a smooth flat surface highly durable against adverse weather conditions.



Advantages:

- Premium quality and durability concrete paint
- Direct application on concrete, plaster, brick and other alkaline surfaces
- Available in white and 4 ready-made shades

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS

Viscosity

110 ± 10 KU (ASTM D 562, 25°C)



Density

1,49 ± 0,02 Kg / L (ISO 2811) for the white

Gloss

< 5 units @ 60° (ISO 2813)

COVERAGE



One coat

15-17 m²/L



Two coats

8-9 m²/L

PACKAGING

White	750 mL	3 L	10 L
Red terracotta, cement, anthracite, steel	750 mL	3 L	10 L

FINISH

Mat	Satin	Gloss
✓		
Mat Finish		

DILUTION



Water

8-10%

ΧΡΟΝΟΣ ΣΤΕΓΝΩΜΑΤΟΣ



Touch dry

30-60 min

Recoat


3-4 h

COLOURS

White, red terracotta, cement, anthracite, steel



FAN DECKS – COLOR CARDS



EXTERIOR USE – CEMENT PAINTS

APPLICATION

APPLICATION FIELD

For any cement surface.

PREPARATION



Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.

To fill any cracks or holes use Acrylic Putty.



Old surfaces previously covered with water paints or distempers (lime wash or ceiling white) should be primed with Acrylan Unco Eco, Durovit or Vitosin.



New surfaces made of plaster, concrete, cement, plasterboard, etc. should be first primed with Durovit or Acrylan Unco Eco.



STEPS

1

Dilute 8-10% with water and stir well before use.

2

Apply the first coat by brush, roller or airless spray gun.

3

Recoat after 3-4 hours.

TIPS

- Application at 5-35°C and <70% RH. Don't apply if there is a risk of rain/frost in the next 48 hours.
- Allow new concrete surfaces to cure a minimum of 30 days prior to paint application.
- Allow at least 3 weeks before cleaning and washing newly painted surfaces

with Cement Paint. Wash gently with water using a soft sponge. In case of tough stains, use a mild colourless detergent or soapy water.

- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Minimize paint wastage by estimating

how much paint you will need.

- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Exterior walls of mineral substrate" VOC content limit **40 g/L**. Maximum VOC content **39 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C

Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

