

# CHASSIS COAT

## Anticorrosive Solvent-Based Paint For Chassis/Frames

It is a quick drying, durable solvent-based paint. It provides great protection against corrosion and excellent fastness to grease, lubricating oils and petroleum compounds. It offers great adhesion, elasticity and has great impact resistance. Suitable for painting chassis of cars and metal surfaces.



### Advantages:

- Ideal for vehicle chassis and new metal surfaces
- Fast drying with excellent resistance to fuels and washing
- Can also be used as anticorrosive undercoat

## PRODUCT FEATURES

### TECHNICAL CHARACTERISTICS



#### Viscosity

80 ± 5 KU (ASTM D 562, 25°C)

#### Density

1,35 ± 0,02 Kg / L (ISO 2811)  
for white

#### Gloss

10 - 40 units @ 60°C  
(ISO 2813)

### COVERAGE



#### One coat

12-14 m<sup>2</sup>/L



#### Two coats

6-7 m<sup>2</sup>/L

### FINISH

| Mat | Satin | Gloss |
|-----|-------|-------|
| ✓   | ✓     |       |

### DILUTION



#### Up to 5%

- For brushing with Brush Solvent T300
- For spraying with Spray Gun Solvent T350

### DRYING TIME



#### Touch dry

1-2 h

#### Recoat

20-24 h

### COLOURS

Grey, Brown  
(Mat Finish)

Black, White  
(Satin Finish)



### PACKAGING

|                              |        |       |
|------------------------------|--------|-------|
| White, Grey,<br>Black, Brown | 750 mL | 2,5 L |
|------------------------------|--------|-------|



# METAL SURFACES

## APPLICATION

### APPLICATION FIELD

For vehicle chassis and new metal surfaces, can also be used as anticorrosive undercoat.

### PREPARATION



**Surfaces should be** cleaned with Brush Solvent T300, be smooth and dry, free from dust, grease or rust and sanded.



**Glossy metal surfaces** (aluminum, galvanized steel etc) should be first coated with Primer for Glossy Surfaces or Wash Primer.



### STEPS

1

Dilute up to 5% for brushing with Brush Solvent T300 or for spraying with Spray Gun solvent T350 and stir well before use.

2

Apply the first coat by brush, roller or spray gun.

3

Recoat after 20-24 hours.

### TIPS

- Application at 5-35°C and <80% RH. For exterior use, don't apply if there is a risk of rain/frost in the next 48 hours.
- Clean rollers, brushes with Brush Solvent T300 and then with soapy water or detergent. Use Spray Gun Solvent T350 to clean spray guns.

- Allow at least 30 days before cleaning and washing newly painted surfaces with Chassis coat.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the

- container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

## ADDITIONAL INFORMATION

### VOCs (Volatile Organic Compounds)



"One-pack performance coatings". VOC content limit **500 g/L**. Maximum VOC content **495 g/L** VOCs (ready for use product).

### PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

### STORAGE



**5°C-38°C**

Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

**+30.210.5589.400**  
TECHNICAL SUPPORT

**ISO 9001**  
14001  
CERTIFIED 45001

