

# DECKING OIL

## Penetrating Oil For Exterior Wooden Decks

Polyurethane modified protective penetration oil, enriched with wax. Used for waterproofing and protection of wooden decks. Penetrates deep into wood pores, prevents the penetration of water and shows off its natural appearance. It has high resistance to chemicals, adverse weather conditions and stresses.



Paints with polyurethane resins for enhanced durability

**Advantages:**

- For waterproofing and protection of wooden decks
- High resistance to chemicals and adverse weather conditions

### PRODUCT FEATURES

#### TECHNICAL CHARACTERISTICS



**Viscosity**

15 - 30 sec (FORD CUP#4, 25° C)

**Density**

0,86 ± 0,02 Kg / L (ISO 2811)

#### FINISH

Natural	Satin	Gloss
✓		
Natural finish		

#### DILUTION




**Undiluted**

Ready for use

#### COLOURS

Colorless




#### COVERAGE



**One coat**

12-16 m<sup>2</sup>/L



**Two coats**

6-8 m<sup>2</sup>/L

#### DRYING TIME



**Touch dry**

2-3 h

**Recoat**

48 h

#### PACKAGING

Colorless	2,5 L	5 L
-----------	-------	-----



# WOOD PROTECTION

## APPLICATION

### APPLICATION FIELD

For wooden decks.

### PREPARATION



**Surfaces** should be smooth, clean, dry, free from grease, rosins or old varnishes.



### STEPS

**1** Stir well before use.

**2** Apply one coat by brush or piece of cloth without dilution. Wipe excess material after 5 minutes with a dry cloth.

**3** Apply a second coat for tough wood or when wood is exposed to adverse weather conditions after 48 hours.

### TIPS

- Application at 5-35°C and <80% RH and wood moisture should not exceed 18%.
- Clean brushes with Brush Solvent T300 and then with soapy water or detergent.

- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

## ADDITIONAL INFORMATION

### VOCs (Volatile Organic Compounds)



"Binding primers", VOC content limit **750 g/L**. Maximum VOC content **450 g/L** VOCs (ready for use product).

### PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

### STORAGE



**5°C-38°C**  
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

**+30.210.5589.400**  
TECHNICAL SUPPORT

