

DELAC

Stone Protective Stain

Transparent acrylic stone varnish, suitable for interior and exterior use. It penetrates the surface so it does not turn yellow or peel. It enhances the natural colour of the surface and protects the stone from humidity and stain absorption. Delac is suitable for all stones or pavement plates, natural or artificial (Eleftheroupolis, Karystou, Piliou, etc.), heat resistant bricks, roof tiles, pore stones, decorative bricks, cement, etc.



Advantages:

- Stone penetration varnish for exterior and interior use
- Enhances the natural surface coloring and protects from humidity and stain absorption

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

30 ± 5 sec (FORD CUP#4, 25° C)

Density


0,83 ± 0,02 Kg / L (ISO 2811)

COVERAGE



One coat

10-12 m²/L



Two coats

5-6 m²/L

PACKAGING

Colorless

750 mL

2.5 L



FINISH

Natural

Satin

Gloss



Natural finish

DILUTION



Undiluted

Ready for use

DRYING TIME



Touch dry

1-2 h

Recoat

3-4 h

COLOURS

Colorless



WOOD PROTECTION

APPLICATION

APPLICATION FIELD

For all stones or pavement plates, natural or artificial.

PREPARATION



Surfaces should be smooth, clean, dry, free from grease, dust or old varnishes.



STEPS

1 Stir well before use.

2 Apply the first coat by brush, roller or spray gun.

3 Recoat after 3-4 hours.

TIPS

- Application at 5-35°C and <80% RH. For exterior use, do not apply if there is a risk of rain/frost in the next 48 hours.
- Clean rollers, brushes with Brush Solvent T300 and then with soapy water or detergent. Use Spray Gun Solvent T350

- to clean spray guns.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Binding primers", VOC content limit **750 g/L**. Maximum VOC content **699 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

