

GALVANIZE

Cold Galvanizing Primer

It is an excellent anticorrosive epoxy primer, rich in zinc dust. It gives high and long lasting anticorrosive protection. It is suitable for priming metallic surfaces such as pumps, pipes and metallic constructions in industrial environment and seaside areas.



Advantages:

- Suitable for metal constructions in industrial environments and seaside areas
- High long-lasting anticorrosive protection

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

90 ± 5 KU (ASTM D 562, 25°C)

Density

1,95 ± 0,02 Kg / L (ISO 2811)

APPLICATION

For priming metallic surfaces such as pumps, pipes and metallic constructions

COLOURS

Grey



COVERAGE



One coat

7-9 m²/L

Two coats

4-5 m²/L

DILUTION



Up to 5%

- With Spray Gun Solvent T350

DRYING TIME



Touch dry
45-60 min

For top coat application
9-12 h

PACKAGING

Grey

375 mL

750 mL



SURFACE PREPARATION

APPLICATION

PREPARATION



Surfaces should be cleaned with Brush Solvent T 300, be smooth and dry, free from dust, grease or rust and sanded (for newly galvanized surfaces a good sanding is required).



STEPS OF APPLICATION

1

Dilute up to 5% with Spray Gun Solvent T350 and stir well before use.

2

Apply one or two coats by brush, roller or spray gun.

TOP COAT APPLICATION



After 9-12 hours the surface is sanded using a suitable sandpaper. Wipe surface to clean off loose dust particles and apply any enamel paint for metal surfaces.

Recommend:

- Solvent-based enamel paint Verolac, Heavy Metal Silicon



TIPS

- Application at 5-35°C and <70% RH. Don't apply if there is a risk of rain/frost in the next 48 hours.
- Clean rollers, brushes and spray guns with Spray Gun Solvent T-350 and then with soapy water or detergent.

- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into

ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"One-pack performance coatings"
VOC content limit **500 g/L**. Maximum VOC content **499 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C

Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

