

GYPSUM BOARD PRIMER

High Quality White Gypsum-Board Primer

Water based acrylic primer for interior use with excellent filling properties on plaster-board surfaces and every other interior surface such as plaster, concrete etc. due to its exceptional filling properties, the absorbency difference between the gypsum-board and all the surrounding surfaces to be painted is compensated. Moreover, it covers completely any unevenness of the plaster-boards' paper. Surfaces primed with Gypsum Board Primer can be painted with any water-based decorative paint resulting in an excellent and even finishing, even when only a single layer of primer is applied



Advantages:

- Exceptional filling properties, fully equalizes absorbency differences between construction materials
- Perfect one-coat finish for interior use only

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

105 ± 5 KU (ASTM D 562, 25°C)

Density

1,72 ± 0,02 Kg / L (ISO 2811)

APPLICATION

For plaster-board surfaces and every other interior surface such as plaster, concrete etc..

COLOURS

White



COVERAGE



One coat

12-14 m²/L

DILUTION



Water

- 5-10 % for brushing
- 10-15% for spraying

DRYING TIME



Touch dry
30-60 min

For top coat application
6-8 h

PACKAGING

White

3 L

10 L



SURFACE PREPARATION

APPLICATION

PREPARATION



Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.



To fill any cracks or holes use Visto or Acrylic Putty. Wet sanding is recommended for the surface preparation.



STEPS OF APPLICATION

1

Dilute 5-10% with water for roller/brush or 10-15% for airless spray gun and stir well before use.

2

Apply one coat by brush, roller or airless spray gun.

TOP COAT APPLICATION



Coat after 4-6 hours with water-based emulsion paints. Recommend: Vitex Classic, Vitex with Teflon™ or Vitex Eco (mat finish) or with Vitex Satin Eco (satin finish).



TIPS

- Application at 5-35°C and <80% RH.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Minimize paint wastage by estimating

how much paint you will need.
• Recover unused paint for re-use. After paint application, seal the container and store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Primers" VOC content limit **30 g/L**.
Maximum VOC content **22 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

