

PRIMER - 100% ACRYLIC

Waterproofing Acrylic Primer Water-Based

Semi-transparent water-based primer of 100% acrylic resins. It is used as an undercoat for Vitex's water-based paints (emulsion, acrylic, cement paints, relief, etc.). It is very easy to apply and has high spreading rate. It improves the appearance, hiding power and weather resistance of the final coat. It is a suitable primer for alkaline surfaces which impregnates and stabilizes them. Low odour product during its application because it does not contain ammonia.



Advantages:

- Great adhesion on surfaces
- High spreading rate and user friendly application
- Dilution 3-4 parts water - 1 part primer

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

70 ± 5 KU (ASTM D 562, 25°C)

Density

1,03 ± 0,02 Kg / L (ISO 2811)

APPLICATION

For surfaces such as plaster, concrete, bricks, plaster boards etc. and coated surfaces.

COLOURS

Semi - transparent



COVERAGE



One coat

18-20 m²/L

DILUTION



Water

300-400 %

DRYING TIME



Touch dry

15-30 min

For top coat application

4-6 h

PACKAGING

Semi-Transparent	750 mL	3 L	10 L
------------------	--------	-----	------



SURFACE PREPARATION

APPLICATION

PREPARATION



Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.



To fill any cracks or holes use Visto or Acrylic Putty. Wet sanding is recommended for the surface preparation.



STEPS OF APPLICATION

1

Dilute 300-400% with water and stir well before use.

2

Apply one coat by brush, roller or airless spray gun.

TOP COAT APPLICATION



Coat after 4-6 hours with water-based paints of interior use
Recommend:
Vitex Classic, Vitex with Teflon™ or Vitex Eco (mat finish) or with Vitex Satin Eco (satin finish).



TIPS

- Application at 5-35°C and <80% RH.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Minimize paint wastage by estimating

how much paint you will need.
• Recover unused paint for re-use. After paint application, seal the container and store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Binding primers" VOC content limit **30 g/L**.
Maximum VOC content **6 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request.
Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

