

RADIATER

Paint For Heated Metal Surfaces

Special, high gloss, white, alkyd-based enamel, suitable for coating heated metal surfaces, such as radiators, boiler covers, etc. It is resistant to temperatures up to 100°C without yellowing or peeling. Offers great hiding power, elasticity, good levelling properties and excellent adhesion.



Advantages:

- Ideal for radiators and boiler covers
- No primer needed
- Excellent durability up to 100°C
- No yellowing or peeling

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

70 ± 5 KU (ASTM D 562, 25°C)

Density

1,21 ± 0,02 Kg / L (ISO 2811)
for white

Gloss

> 90 units @ 60°C (ISO 2813)

COVERAGE



One coat

14-16 m²/L



Two coats

7-8 m²/L

PACKAGING

White

750 mL

2.5 L



FINISH

Mat

Satin

Gloss



Gloss Finish

DILUTION



Up to 5%

- For brushing with Brush Solvent T300
- For spraying with Spray Gun Solvent T350

DRYING TIME



Touch dry

2-3 h

Recoat

20-24 h

COLOURS

White



METAL SURFACES

APPLICATION

APPLICATION FIELD

For heated metal surfaces such as radiators, boiler covers, e.t.c..

PREPARATION



Surfaces should be cleaned with Brush Solvent T 300, be smooth and dry, free from dust, grease or rust and sanded.



STEPS

1

Dilute up to 5% for brushing with Brush Solvent T300 or for spraying with Spray Gun Solvent T350 and stir well before use.

2

Apply the first coat by brush, roller or spray gun.

3

Recoat after 20-24 hours.

TIPS

- Application at 5-35°C and <80% RH.
- Clean rollers, brushes with Brush Solvent T300 and then with soapy water or detergent. Use Spray Gun Solvent T350 to clean spray guns.
- Allow at least 30 days before

cleaning and washing newly painted surfaces with Radiater.

- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use.

After paint application, seal the container and store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"One-pack performance coatings".
VOC content limit **500 g/L**. Maximum
VOC content **495 g/L** VOCs (ready for
use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request.
Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C

Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

