

ROAD MARKING PAINT

Acrylic Road Marking Paint

Fast drying acrylic paint, suitable for road, parking and field marking. It has strong adhesion and excellent durability. For higher reflectivity recommended application in combination with special glass beads.

Advantages:

- Ideal for marking roads, parkings and fields
- Fast drying and high reflectance
- Excellent resistance to weathering



PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

85 ± 10 KU (ASTM D 562, 25°C)

Density

1,48 ± 0,02 Kg / L (ISO 2811)

for white

1,41 ± 0,02 Kg / L (ISO 2811)

for yellow


DILUTION



5-10%

With Spray Gun
Solvent T350 or
Nitro Solvent
T400

COVERAGE



For wet film

thickness 200 µm

2-4 m²/L

For wet film

thickness 400 µm

1-2 m²/L


PACKAGING

White, Yellow	750 mL	2,5 L	25Kg
------------------	--------	-------	------



COLOURS

White, Yellow



* Other shades are available upon client's request.

DRYING TIME



Touch dry

10-20 min

Recoat

2-4 h

APPLICATION

APPLICATION FIELD

For road, parking and field marking.

PREPARATION



Surfaces must be clean, dry and smooth, free from dust, grease or loose material.

SPECIAL APPLICATIONS

APPLICATION

STEPS

1

Dilute up to 5-10 % with Spray Gun Solvent T350 or Nitro Solvent T400. and stir well before use. Apply the first coat by road marking machinery, roller, brush or spray gun.

2

Recoat after 2-4 h depending on the application thickness. Glass beads are spread evenly after the application before the paint dries. In 1 Kg paint add 300-400 gr glass beads.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



Maximum VOC content **495 g/L** VOCs (ready for use product).

PRECAUTIONS



*** Only for professional use.** Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request.
Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT



VITEX S.A., P.O. Box. 139 Imeros Topos, Aspropyrgos GR 193 00 | Tel. +30 210 5589500, Fax +30 210 4835007 | www.vitex.gr

Version: 12.2020 (This datasheet supersedes all previous versions)