

VISTA ACRYLIC

Acrylic paint for general use

Acrylic paint, for exterior use, based on acrylic copolymer resins. It exhibits great hiding power and high spreading capacity. It is easy to apply with very good leveling and it produces a smooth flat surface.



Advantages:

- High spreading rate and hiding power
- Ideal for exterior surfaces that require frequent recoating

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

110 ± 10 KU (ASTM D 562, 25°C)


Density

1,60 ± 0,02 Kg / L (ISO 2811)
for white

Gloss

< 5 units @ 60° (ISO 2813)

COVERAGE



One coat

10-12 m²/L



Two coats

5-6 m²/L

PACKAGING

White	3 L	9 L	15 L
Bases	3 L	9 L	

FINISH

Mat	Satin	Gloss
✓		

Mat Finish

DILUTION



Water

0-10%

DRYING TIME



Touch dry

30-60 min

Recoat

3-4 h

COLOURS

1500 +

White and unlimited number of shades through Vitex Coloring System



COLOR CARDS - FANDECKS:



APPLICATION

APPLICATION FIELD

For the painting and renovation of masonry and cement substrates when the proper primer is used.

PREPARATION



Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.



To fill any cracks or holes use Acrylic Putty.



Old surfaces should be primed, on a case by case basis, with Vitosin, Durovit or Acrylan Unco Eco.

New surfaces made of plaster, concrete, cement, plasterboard, etc. should be first primed with Acrylan Unco Eco.



STEPS

- 1 Dilute up to 10% with water and stir well before use.
- 2 Apply the first coat by brush, roller or airless spray gun.
- 3 Recoat after 3-4 hours.

TIPS

- Application at 5-35°C and <70% RH. Don't apply if there is a risk of rain/frost in the next 48 hours.
- Allow new plaster or concrete surfaces to cure a minimum of 30 days prior to paint application.
- The product must be exclusively tinted through **Vitex Coloring** System in the recommended base.
- Allow at least 3 weeks before cleaning and washing newly painted surfaces with Vista Acrylic. Wash gently with water using a soft sponge. In case of tough stains, use a mild colourless detergent or soapy water.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Exterior walls of mineral substrate". VOC content limit **40 g/L**. Maximum VOC content **39 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

