

VISTO READY FINE

Ready To Use Finishing Putty

Ready to use white putty of large surfaces in paste, suitable for interior walls and ceilings of plaster, gypsum-boards and concrete surfaces and for joint finishing. It has excellent filling capacity, applied and sanded very easily creating a very smooth, uniform and cohesive surface paintable with emulsion or enamel paints.



Advantages:

- Ready to use
- Very easy application and sanding
- Perfect coverage
- Smooth and even finish
- Can be stored after opening
- Clean application with minimum dust

PRODUCT FEATURES

COVERAGE



1 kg/m²
for 0,5
mm layer
thickness

DRYING TIME



Touch dry
2-3 h

COLOURS

White



PACKAGING

White

5 kg

18 kg



VITEX S.A.
P.O. BOX 139 IMEROS TOPOS ASPROPYRGOS
GR 19300

VISTO READY FINE
17

DoP No : VIT-CPR-0032.1

Type 3A -EN 13963
Jointing materials for gypsum
plasterboards

Reaction to fire	A2-s1,d0
------------------	----------

Flexural strength	>50 N
-------------------	-------

APPLICATION

APPLICATION FIELD

Finishing putty for interior walls and ceilings of plaster, gypsum-boards and concrete surfaces.

PREPARATION



Surfaces must be must be clean, dry and smooth, free from dust, grease, loose material.

CONSTRUCTION APPLICATIONS - PUTTIES

APPLICATION

STEPS

1

The putty is ready to use. Stir well before use and add water where is needed.

2

Apply the first coat using a spatula/knife or airless gun and let it dry.

3

After 4-6 hours apply the second coat crosswise and let it dry. Sand after 3-4 hours with a sandpaper No 200 or higher size and clean the surface.

TIPS

- Application at 5-35°C and <80% RH.
- After the application, seal the container and store it for future use.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Do not dispose of liquid waste into ground water table. Unused material requires special handling for safe disposal.

ADDITIONAL INFORMATION

STORAGE



5°C-38°C

Containers must be kept closed in a shady place away from direct sunlight, maximum 24 months from date of production.

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.



VITEX S.A., P.O. Box. 139 Imeros Topos, Aspropyrgos GR 193 00 | Tel. +30 210 5589500, Fax +30 210 4835007 | www.vitex.gr

+30.210.5589.400

TECHNICAL SUPPORT



Version: 12.2020 (This datasheet supersedes all previous versions)